



PO BOX 16458 • FRESNO CA 93755

MATERIAL SAFETY DATA SHEET

PRODUCT/TRADE NAME:

ProNatural® Micronized Sulfur

I. NAME

PRODUCT/TRADE NAME: ProNatural Micronized Sulfur
EPA REGISTRATION #: 2935-407
CHEMICAL NAME/Common Name:
Sulfur/Sulfur

II. HAZARDOUS INGREDIENTS

| | CAS# | OSHA PEL | ACGIH TLV |
|--------|-----------|----------|-----------|
| Sulfur | 7704-34-9 | NE | NE |

III. PHYSICAL DATA

SPECIFIC GRAVITY (H₂O = 1): NA
MELTING POINT: 119 Deg. F
VAPOR DENSITY (AIR = 1): NA
% VOLATILES BY VOL.: NA
ODOR: Sulfur
APPEARANCE: Yellow Powder
FLASH POINT/METHOD: 374 Deg. F (Dust)
VAPOR PRESSURE (mmHg): NA
SOLUBILITY IN H₂O: Insoluble

IV. FIRE & EXPLOSION HAZARD

EXTINGUISHING MEDIA: Water Fog Foam Alcohol Foam
 CO₂ Dry Chemical Other
FIRE FIGHTING PRECAUTIONS & HAZARDS:
Fight fire upwind. Wear positive pressure self-contained breathing apparatus and full protective equipment. Avoid solid streams of water which may stir dust clouds or spread fire. Dust may form explosive mixture with air. Dike to prevent entering drains, sewers, or water courses. Evacuate people downwind from fire.

V. CARCINOGEN STATUS

OSHA NTP IARC No Listing Type

VI. REACTIVITY

Stable HAZARDOUS POLYMERIZATION
 Unstable May Occur Will Not Occur
AVOID: Oxidizers, Powdered carbon
HAZARDOUS DECOMPOSITION PRODUCTS: CO_x, SO_x, H₂S

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL: Do not use flares in area. Wear appropriate eye protection. Control dust with water fog. Vacuum or sweep material into dry container.
DECONTAMINATION: Treat area with water until clean.
ENVIRONMENTAL HAZARDS: None.
DISPOSAL: Dispose of material in accordance with Federal, State and local regulations.

VIII. HEALTH PRECAUTION DATA

INGESTION: Do not ingest. Wash thoroughly before eating, drinking or smoking. Do not store near food or feed.
INHALATION: Nuisance dust PEL/TLV 15 mg/m³ total dust. 15 mg/m³ respirable dust. Wear approved respiratory protection for exposures above the PEL/TLV.
SKIN ABSORPTION: May cause skin irritation. Remove from skin with soap and water.
EYE EXPOSURE: Sulfur may cause eye irritation. Do not rub eyes if exposed. Flush with water for a minimum of 15 minutes. Wear appropriate eye protection to reduce exposure.
EFFECTS OF OVEREXPOSURE: May cause skin or eye irritation. If ingested, it may cause vomiting and diarrhea. Chronic exposure may cause skin and eye irritation. Preexisting medical conditions involving the above symptoms may be aggravated by exposure.
FIRST AID: In all cases, get prompt medical attention. If ingested, give several glasses of water. For eye exposure, irrigate eyes a minimum of 15 minutes with water. For skin exposure, remove contaminated clothing and wash with soap and water. If inhaled, remove victim to fresh air, and administer CPR if necessary.

IX. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use only NIOSH/MSHA - approved respiratory protection for nuisance particulates up to 10 times the PEL/TLV. Positive pressure self-contained breathing apparatus should be used for confined space entry and exposures above 10 times the PEL/TLV.
PERSONAL PROTECTIVE EQUIPMENT: Chemical-resistant gloves, long-sleeved coveralls, safety goggles or glasses with side shields and brow protection.
VENTILATION: Local ventilation recommended for manufacture and formulation.

X. SPECIAL PRECAUTIONS

Keep out of the reach of children. Read and follow all label instructions. Store in tightly closed containers. This product contains clay and small amounts of crystalline silica may be found. Inhalation of large amounts of crystalline silica may cause pulmonary fibrosis. Sulfur dust can be explosive. Do not allow dust to build up. Keep clear of ignition sources.

XI. REGULATORY DATA

SARA HAZARD CLASS: Acute Chronic Flammable
 Pressure Reactive None

SARA 313: Yes No Chemical:

SARA 302: Yes No Chemical:

TPQ:

CERCLA: Yes No Chemical:

RQ:

RCRA: Yes No

NFPA HAZARD RATING:

Health: [1]

Fire: [2]

Reactivity: [0]

Special: []

HMS CODES:

Health: [1]

Fire: [2]

Reactivity: [0]

NFPA HAZARD RATING SCALE:

0 = Minimal 3 = Serious

1 = Slight 4 = Severe

2 = Moderate

HMS HAZARD RATING SCALE:

0 = Minimal 3 = Serious

1 = Slight 4 = Severe

2 = Moderate

DATE PREPARED: October 11, 2005

REVISED DATE:

Notice: This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

*Technical Material NE - Not Established NA - Not Applicable

24 Hour Emergency Phone Number
CHEMTREC: (800) 424-9300

